



A	B	C	D	E	F
7.2"	11.6"	12.6"	8.2"	4.33"	2"
183mm	295mm	320mm	209mm	110mm	51mm

## ORDERING INFORMATION

Series	LED Color	Model	Options
LP	R (red) G (green)	HT (AC Only) SA (self powered)	B (black)

EXAMPLE: PX-R-SA-B  
DESCRIPTION: PACO exit sign , self powered, Red LED , black housing, damp location.

## PRODUCT OVERVIEW

The **LOWPRO** series thermoplastic exit features performance and reliability in a compact, attractive and low profile package. Configured with red or green LED's, the **LOWPRO** provides a bright and even EXIT. The thermoplastic housing comes in white as standard; optional black is available. The quick connect installation system allows for effortless surface mount installation. The **LOWPRO** is a universal exit available with or without battery back-up. Standard with mounting canopy and extra stencil face plate.

## INSTALLATION

The **LOWPRO** exit is designed for surface wall or ceiling installations. Suitable for indoor / damp location environments.

## EXTERNAL SPECIFICATIONS

The **LOWPRO** series is constructed from high impact, injection molded thermoplastic. White finish is standard. Field adjustable chevrons are standard. The **LOWPRO** series can be universally

mounted single or double face (extra faceplate included). The SA version includes an integrated test switch /monitor LED, which gives immediate unit status.

## INTERNAL SPECIFICATIONS

**AC ONLY:** Standard 120/277VAC input.

**SELF-POWERED:** Standard 120/277VAC input. The **LOWPRO** self-powered version uses a rechargeable, maintenance free 3.6V 900mAH nickel cadmium battery. The circuit board features an onboard solid state transformer, low voltage disconnect and brownout protection.

## WARRANTY

The **LOWPRO** series comes with a 3-year factory warranty. Deliberate damage, misuse, improper installation effectively void the warranty. For complete warranty details see online.



**SALES DEPARTMENT**  
(T) 800-480-0707  
sales@emergencylights.net  
www.emergencylights.net

#### **MODERN DESIGN**

LOWPRO series exit provides performance and reliability in a small and modern design. The low profile, rounded corners and an overall reduced size, make the LOWPRO one of the smaller, code compliant exit signs available.

#### **BATTERY TECHNOLOGY**

The LOWPRO series is design with a 3.6V 900mAH maintenance-free sealed nickel cadmium battery that provides minimum emergency duration of 90 minutes. The recharge time of the battery is 24 hours.

#### **ELECTRICAL SPECIFICATIONS**

The LOWPRO series has a universal 120/277VAC solid state transformer. Low voltage disconnect and brownout protection are standard. Red or green LEDs totaling <2W.



#### **MECHANICAL SPECIFICATIONS**

The LOWPRO series is constructed from high impact, injection molded thermoplastic. The housing features field adjustable chevrons and a universal mounting pattern for single or double face configurations. The SA version includes an integrated test switch / monitor LED gives immediate unit status.

#### **SELF-POWERED SERIES**

The LOWPRO self-powered series is designed to operate on battery power in the event of regular / mains power failure. Both the battery and charger are completely contained within the standard sign. There are no external components and no alteration made to the external dimensions of the standard sign. Status is easily determined via an LED that indicates AC-ON. A push button test switch allows maintenance personnel to quickly confirm the operational status of the exit at any time.

#### **WARRANTY**

The LOWPRO series comes with a 3-year factory warranty. Deliberate damage, misuse, improper installation effectively void the warranty. For complete warranty details see online.